



How to remove shade from the headrail

Step 1 : Lower the blind

Step 2 : Take the knotted lift cord out of the bottom ring.

REMARK: Do not remove the knot in the lift cord!

Step 3 : Take the lift cords out of the reinforced rings which are attached to the batten pockets.

Step 4 : Take the hem bar out of the hem bar pocket through the opening that is at the top of the hem bar pocket.

Step 5 : Take the battens out through the ultrasonic buttonholes which are at the side of the batten pockets.

REMARK: Don't lose the spring system. This provides the correct tension in the battens.

Step 6 : Take the blind off the velcro.

Step 7 : Leave the lift cords hanging. DO NOT PULL THE CORDS UP INTO THE SYSTEM (HEADRAIL)!

How to reattach the blind to the headrail:

Step 1 : Reattach the blind onto the velcro.

Step 2 : Place the hem bar in the hem bar pocket.

Step 3 : Place the battens in the batten pockets through the ultrasonic buttonhole. Don't forget to place the spring system on the ends of the battens.

Step 4 : Put the lift cords through the rings. Make sure you don't miss a ring.

Step 5 : Click the knot in the lift cord on the bottom ring.

Step 6 : You can now operate the blind.

Shadow Belgium

Ovenstraat 12, 8800 Roeselare, Belgium

www.shadow-inside.be

"Made in Belgium"